



**POWERFUL**  
**SUSTAINABLE**  
**NO GAS!**



## PKT-8-RHC40

Pneumatic battery nailer  
for nails type RHC from 15 to 40 mm

**Product number:** PKT-8-RHC40

- One device for all applications for direct installation
- Independent of gas cylinder, power cord and air hose for maximum operation
- No subsequent costs for gas, etc.
- For indoor and outdoor use
- Weather and temperature independent
- Environmentally conscious – no CO2 emissions

### Product features:

Fill level indicator, pressure relief, operation via touch display, lock-out safety device, adjustable depth control, fast loading system, fast shot sequences, compact design

**Benefits for the user:** huge time advantage, high flexibility and noticeable cost savings compared to conventional fastening processes that require drilling, cleaning and dowelling.

### Applications:

Dry construction, steel construction, plumbing, heating installation, electrical installation

### Technical Data:

Weight without battery (kg)	5,5
Width (mm)	118
Length (mm)	437
Height (mm)	434
Magazin capacity	4 stripes per 10 nails
Fastening	Nails
Fastening type	RHC
Fastening length (mm)	15 - 40


### Scope of delivery:

**PKT-8-RHC40:** Pneumatic battery nailer PKT-8-RHC40, plastic transport case, refillable air cylinder KT-1000 (only for filling).

**PKT-8-RHC40-SET22:** Pneumatic battery nailer PKT-8-RHC40, plastic transport case, refillable air cylinder KT-1000 (only for filling), 2 pcs. 18 V 2.0-LiHD high-performance battery, charging-station 12-36



U-profile fastening



Tube fastening



Cable fastening



**Suitable fastener:  
Steel-/concrete nails type RHC from 15 to 40 mm**

Article No.	Material	Pcs/Box
RHC-S-NK 30/15	galvanized	1.000
RHC-S-NK 30/17	galvanized	1.000
RHC-S-NK 30/22	galvanized	1.000
RHC-S-NK 30/27	galvanized	1.000
RHC-S-NK 30/32	galvanized	1.000
RHC-L-NK 27/20	galvanized	1.000
RHC-L-NK 27/25	galvanized	1.000
RHC-L-NK 27/30	galvanized	1.000
RHC-L-NK 27/35	galvanized	1.000
RHC-L-NK 27/40	galvanized	1.000

**Technical Data:**

Head size (mm)	5,8 - 6,5
Wire gauge (mm)	2,7 - 3,0
Length (mm)	15 - 40
Material	NK = galvanized
Applications	S = Strong L = Light



Nails type RHC



Type RHC-S for fastenings in steel/concrete



Type RHC-L for fastenings in concrete/stonework e.g.

	RHC-S-NK					RHC-L-NK				
	30/15	30/17	30/22	30/27	30/32	27/20	27/25	27/30	27/35	27/40
	●	●	●	●	●					
	●	●	●	●	●					
	●	●	●	●	●	○	○	○	○	○
	○	○	○	○	○	●	●	●	●	●
	○	○	○	○	○	●	●	●	●	●
	○	○	○	○	○	●	●	●	●	●