
www.picopack.co.kr CS@picopack.co.kr







PRODUCT FEATURES

- CNT digital X-ray tube
- Perfect repeatability
- No stray X-rays (Totally low dose)
- No oil leakage
- Ergonomic and intuitive interfacing

CERTIFICATION STATUS

• ISO 13485 • GMP • FDA510(K)



PRODUCT SPECIFICATIONS

Tube Voltage	70kV	Exposure Time	0.05~1.0s	Total Weight	3.97 lbs (1.8kg)
Tube Current	2mA	Lifespan	200,000 shot	S.S.D.	200mm
Focal Spot (nominal)	0.4	Maximum Duty Cycle	1:30		

www.picopack.co.kr ULTRA SHOR





PRODUCT FEATURES

- Compact head size
- Ergonomic design that minimizes foreign body feeling in the mouth
- High-definition image with 14bits gray scale and best actual resolution
- 3 types of preset image mode for user convenience
- Printing mode with reporting function
- Easy to install software

PRODUCT SPECIFICATIONS

Model	XDP-F350A	XDP-F150A	
1010401	ADF 1 330A	ADF 1 150A	
Dimentions (W x L)	33.7 × 43.4 mm	27 × 37 mm	
Scintillator Technology(CsI)	FOS	FOS	
Active Area(CMOS)	26 × 34 mm	21.6 × 30 mm	
Theoretical Resolution	25 lp/mm		
Pixel Size	20um		
Gray Levels	16,384(@14bits)		
Cable Length	2.5m		
Thickness	5.4mm		
Connection	Standard USB 2.0		

CERTIFICATION STATUS

ISO 13485

GMP

FDA510(K)

MFDS

INTRA_ORAL SENSOR SOFT WARE (CONSOLE VIEWER)

